



BONA

Display Specialist

Character LCD module Series

Display Format	Part No	Variation	Dot Size (W x H mm)	Dot Pitch (W x H mm)	Viewing Area (W x H mm)	Outline Dimension (W x H x T mm)	Built-in Controller	Multiplex / Bias	Page	
8 x 1	MC0801-01	Reflective	1.25 x 1.30	1.30 x 1.35	61.00 x 15.80	84.0x44.0x12.0	KS0066U	1/8 duty 1/4 bias	15	
		EL				84.0x44.0x12.0				
		LED				84.0x44.0x14.0				
	MC0801-02	Reflective	0.83 x 0.93	0.90 x 1.00	45.00 x 14.00	60.0x33.0x8.0	KS0066U	1/8 duty 1/4 bias	16	
8 x 2	MC0802-01	Reflective	0.50 x 0.50	0.57 x 0.57	30.00 x 14.00	40.0x35.5x7.4	KS0066U	1/16 duty 1/5 bias	17	
12 x 2	MC1202-01	Reflective	0.396 x 0.48	0.448 x 0.512	34.0 x 12.0	37.0x23.0x2.0	SPLC093	1/17 duty 1/5 bias	18	
14x2+Icons	MC1402-01	EL	0.48 x 0.48	0.52 x 0.52	48.0 x 11.5	51.0x16.5x 4.1	S6A0074	1/33 duty 1/6 bias	19	
16 x 1	MC1601-01	Reflective	0.60 x 0.75	0.65 x 0.80	64.50 x 13.80	79.5x35.5x9.0	KS0066U	1/16 duty 1/5 bias	20	
		EL				79.5x35.5x9.0				
		LED				79.5x35.5x13.0				
	MC1601-02	Reflective	0.60 x 0.75	0.65 x 0.80	64.50 x 13.80	79.5x35.5x9.0	KS0066U	1/16 duty 1/5 bias	21	
EL		79.5x35.5x9.0								
LED		79.5x35.5x13.0								
16 x 2	MC1602-03	Reflective	0.92 x 1.10	0.98 x 1.16	99.00 x 24.00	122.0x44.0x11.0	KS0066U	1/16 duty 1/5 bias	22	
		EL				122.0x44.0x11.0				
		LED				122.0x44.0x14.0				
		MC1602-04	Reflective	0.55 x 0.65	0.60 x 0.70	65.60 x 16.00	84.0x44.0x9.5	KS0066U	1/16 duty 1/5 bias	23
	EL		84.0x44.0x9.5							
	LED		84.0x44.0x13.0							
		MC1602-13	Reflective	0.55 x 0.50	0.60 x 0.55	65.60 x 16.00	79.5x35.5x10.0	KS0066U	1/16 duty 1/5 bias	24
	EL		79.5x35.5x10.0							
	LED		79.5x35.5x13.0							
		MC1602-17	Reflective	0.55 x 0.65	0.60 x 0.70	65.60 x 16.00	79.5x35.5x9.5	KS0066U	1/16 duty 1/5 bias	25
	EL		79.5x35.5x9.5							
	LED		79.5x35.5x13.0							
		MC1602-18	Reflective	0.55x0.50	0.60x0.55	64.40 x 13.80	79.5x35.5x9.5	KS0066U	1/16 duty 1/5 bias	26
	EL		79.5x35.5x9.5							
	LED		79.5x35.5x13.0							
	MC1602-19	Reflective	0.55x0.60	0.60x0.65	61.0x15.7	65.0x27.7x3.4	NT7603	1/16 duty 1/5 bias	27	
	MC1602-20	EL	0.55x0.60	0.60x0.65	61.0x15.7	65.0x27.7x3.16	ML9042	1/16 duty 1/5 bias	28	
	MC1602-21	Reflective	0.55 x 0.65	0.60 x 0.70	61.0x16.0	85.0x32.5x9.0	KS0066U	1/16 duty 1/5 bias	29	
		EL				85.0x32.5x9.0				
		LED				85.0x32.5x13.0				
16 x 4	MC1604-01	Reflective	0.55 x 0.55	0.60 x 0.60	61.60 x 25.20	87.0x60.0x10.0	KS0066U	1/16 duty 1/5 bias	30	
		EL				87.0x60.0x10.0				
		LED				87.0x60.0x14.0				
	MC1604-02	LED	0.56 x 0.56	0.60 x 0.60	61.80 x 25.20	87.0x60.0x15.0	SPLC780	1/16 duty 1/5 bias	31	
20 x 2	MC2002-01	Reflective	0.60 x 0.65	0.65 x 0.70	85.00 x 19.80	116.0x37.0x10.0	KS0066U	1/16 duty 1/5 bias	32	
		EL				116.0x37.0x10.0				
		LED				116.0x37.0x14.0				
		MC2002-02	Reflective	0.60 x 0.65	0.65 x 0.70	85.00 x 19.80	116.0x39.0x10.0	KS0066U	1/16 duty 1/5 bias	33
	EL		116.0x39.0x10.0							
	LED		116.0x39.0x14.0							
		MC2002-03	Reflective	0.60 x 0.65	0.65 x 0.70	85.00 x 19.80	116.0x37.0x10.0	KS0066U	1/16 duty 1/5 bias	34
	EL		116.0x37.0x10.0							
	LED		116.0x37.0x14.0							

REMARKS:

- Most of the modules have normal and wide operation temperature options.
- For details, please consult our sales engineers or representatives.
- Specifications not listed here can be available upon request
- Temperature Range:
 - Normal Temperature: Storage Temp. = -10 to +60 ; Operating Temp. = +0 to 50 .
 - Wide Temperature: Storage Temp. = -30 to +80 ; Operating Temp. = -20 to 70 .
 - Extended wide temperature: Storage Temp. = -35 to +85 ; Operating Temp. = -30 to 80 .



Character LCD module Series

Display Format	Part No	Variation	Dot Size (W x H mm)	Dot Pitch (W x H mm)	Viewing Area (W x H mm)	Outline Dimension (W x H x T mm)	Built-in Controller	Multiplex / Bias	Page	
20 x 4	MC2004-01	Reflective	0.55 x 0.55	0.60 x 0.60	76.00 x 25.20	98.0x60.0x11.0	KS0066U	1/16 duty 1/5 bias	35	
		EL				98.0x60.0x11.0				
		LED				98.0x60.0x14.0				
	MC2004-02	Reflective	0.76 x 0.89	0.81 x 0.94	98.0 x 40.0	112.0x65.0x11.0	KS0066U	1/16 duty 1/5 bias	36	
		EL				112.0x65.0x11.0				
		LED				112.0x65.0x14.10				
	MC2004-04	LED	0.55 x 0.55	0.60 x 0.60	76.0 x 25.2	98.0x60.0x15.0	S6A0069	1/16 duty 1/5 bias	37	
	24 x 2	MC2402-01	Reflective	0.60 x 0.65	0.65 x 0.70	93.50 x 15.80	118.0x36.0x11.0	KS0066U	1/16 duty 1/5 bias	38
			EL				118.0x36.0x11.0			
LED			118.0x36.0x14.0							
40 x 2	MC4002-01	Reflective	0.60 x 0.65	0.65 x 0.70	154.5 x 15.8	182.0x33.5x11.0	KS0066U	1/16 duty 1/5 bias	39	
		EL				182.0x33.5x11.0				
		LED				182.0x33.5x14.0				
40 x 4	MC4004-01	Reflective	0.50 x 0.55	0.57 x 0.62	147.0 x 29.5	190.0x54.0x11.0	KS0066U	1/16 duty 1/5 bias	40	
		EL				190.0x54.0x11.0				
		LED				190.0x54.0x14.0				

REMARKS:

1. Most of the modules have normal and wide operation temperature options.
2. For details, please consult our sales engineers or representatives.
3. Specifications not listed here can be available upon request
4. Temperature Range:
 - Normal Temperature: Storage Temp. = -10 to +60 ; Operating Temp. = +0 to 50 .
 - Wide Temperature: Storage Temp. = -30 to +80 ; Operating Temp. = -20 to 70 .
 - Extended wide temperature: Storage Temp. = -35 to +85 ; Operating Temp. = -30 to 80 .